

NK AUTOMATION

NK Fencing Ltd

(Head office)

40 Trailcock Road

Carrickfergus

Co. Antrim

BT38 7NU

t: +44 28 9335 1172

f: +44 28 9336 4336

e: mail@nkfencing.com

w: www.nkautomation.co.uk

(Dublin depot)

Backweston

Leixlip

Co. Dublin

Ireland

t: +353 1 626 9000

f: +353 1 624 5465

e: mail@nkfencing.ie

w: www.nkautomation.ie

NK BI-FOLDING GATE



NK BI-FOLDING GATE

GENERAL SPECIFICATIONS

Bi-folding swinging gate leaves, framework construction comprising RHS steel section.

INFILL: CHS Tubular section or Mesh infill to suit fenceline.

AVAILABLE HEIGHTS: 2m, 2.4m, 2.7m and 3m.

AVAILABLE WIDTHS: Single leaf spans 2m, 2.5m, 3m, 3.5m. Double leaf spans 3m, 3.5m, 4m, 5m, 5.5m, 6m, 6.5m, 7.5m.

OPERATION TIME: 3 - 6 seconds (variable due to span).

POWER UNIT: 3 phase motor, worm & wheel gearing with direct drive shaft to gate leaf.

FINISH: Galvanised to BS EN 1461 : 2009 & Polyester powder coated to BS EN 13438 : 2005.

STANDARD CONTROL: 1 Nr deadmans keyswitch to inside of cabinet, 1 Nr Radio receiver and 2 Nr remote handheld transmitters, 1 Nr seven day timer.

STANDARD SAFETY: 6 Nr safety edges, dual height photocells mounted on the support structure, covering clear opening inside & outside the gate leaf, flashing light.

*All dimensions represent nominal values.

For further details on our complete automation range along with technical specifications, please visit our website at:

www.nkautomation.co.uk

KEY FEATURES: The NK Bi-folding swinging gate guarantees smooth, rapid and quiet gate movement, as a result of the individually mounted drive shaft mechanisms.

A securely concealed manual release mechanism is included as standard allowing manual control of the gate in the event of a power failure.

All NK Automation products are fully compliant with BS/EN 12453 safety features as directed from the European Standards and Regulations.

ADDITIONAL ITEMS: Control Options: Stainless steel Intercom, Stainless steel Videocom, Stainless steel key pad, Stand alone prox reader, Network prox reader and additional Hand held radio Transmitters.

NK AUTOMATION - Access control made simple

RELATED PRODUCTS

OTHER PRODUCTS:

- ▶ NK Sliding Gates
- ▶ NK Turnstiles
- ▶ NK Traffic Barriers
- ▶ NK Bollards
- ▶ NK Swinging Barriers
- ▶ NK Safety Gates

STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct.

BLACK
RAL 9005

GREY
RAL 7037

BLUE
RAL 5010

WHITE
RAL 9010

GREEN
RAL 6005

RED
RAL 3000

YELLOW
RAL 1006

BROWN
RAL 8019